

STNH | Handrail Strip Installation

For 1 ½ - 2" round railing made of steel, wood, stainless. Perfect for high-rise buildings, schools, stadiums, theaters, homes and businesses.

For compliant placement of railing markings, consult your applicable local or national codes (2009, 2012 IBC section 1024 + 2015 IBC section 1025).

Installation Steps:

1. Thoroughly clean the surface area where the strip will be installed with a dry cloth and non-residue cleaning compound to remove and loose particles and dirt. Surface must be dry and dust free.
2. Cut to length with scissors.
3. Peel the backing from the Handrail Strip without touching the adhesive.
4. Place the strip and starting from one end to the other, firmly press the strip onto the handrail. Be sure that the strip has full contact with the railing.

Installation Inspection:

Maintain by cleaning as needed to prevent dirt, etc. from inhibiting the performance of the Photo-Glo.

May be cleaned by mopping, damp cloth or by using high-pressure water (NO STEAM CLEANING). Use mild, non-abrasive cleaners. Do not use highly alkaline $\text{pH} > 8$ or acidic cleaners $\text{pH} < 5$. Rinse after applying cleaners. Wipe with a clean cotton cloth to dry.

Photo-Glo Charge Instruction:

Minimum of 1-foot candle (11 Lux) of fluorescent, incandescent or LED (light emitting diode) for 60 Minutes is required to charge Photo-Glo.

Control of lighting restricted to authorized personnel. Reliable external illumination is always required during building occupancy.

Do not use Photo-Glo where the ambient illumination level is less than 1-foot candle (11 Lux).

If you have further questions, please contact us:

Call: 1-855-723-6673 Email: sales@safetnose.com